

# 8ft (Jointable) Glass Tube Type B



## FEATURES AND BENEFITS

- Two parts combined to be one tube(Assembled together before delivery)
- Current leakage protection, passed UL1993 new standard(Review ID# 1993-2018-006)
- Double-ended ballast bypass
- Meet NSF requirements
- Automatic production, high product consistency and low manufacture costs

## PRODUCT SPECIFICATIONS

Size	T8
End cap	FA8
Body	Glass
Lens	Frosted
Input Voltage	120-277vac,50/60hz
Power Factor	0.96
Available colors	5000K
CRI	Ra83
Dimming	Non-dimmable
Lifetime	50,000hours
Warranty	5 Year
Environmental Requirements	Operationtemp:-20°-45°C Storage temp:-20°to45°C Relative Humidity:45%-85% Non-corrosive environments

## SPECIFICATION

Item No.	TypeB Power (±10%)	CCT	TypeB Lumen (±10%)	CRI	Voltage	Frequency	PF	Beam angle	Target lamp
PV-8FT-42WBSL-50K	42W	5000K	5500lm	Ra83	AC120-277V	50/60Hz	0.96	220°	59W/96T8

## WIRING DIAGRAM:

TYPE B(AC directly, double end ballast bypass) - Assembly introduction:

